

BRAVO RTAI

COLOUR REVERSE TRANSFER PRINTER

600 dpi (dots per inch; over-the-edge printing)

LAMINATION possibilities without a LAMINATOR

Unique Features

- Patch retransfer film 0.7 Mil for high card life without additional lam module
- Holographic retransfer film (standard & customised) to save on cost + time
- Special colour ribbons capable of printing Silver and Gold on card
- Unique printing technology on transparent card (innovative technology)
- Wooden cards (specially treated) can be used in the printer to sustain Eco-friendliness
- External tactile printing module as a desired overt security on card (generic/customised)

Introducing **HOLO-MET™** (metallic lustre effect)

Enhance visual ID security using special holo-met secure ribbons.





User-friendly LCD & Keypad

Large rotate button, easy maintenance

High-Capacity consumables, easy replacement



Input Hopper

Card Feeder LOCK, prevents card tampering

Manual Card Feed Option

- Rejected Card Exit, promotes quality control

Durable alloy construction, solid industrial usage

Specifications:

Printing Method	Color dye sublimation retransfer technology
Resolution	600 DPI
Print Capability	Single/Dual Sided, Over-the-Edge, Photo quality
Print Speed	Single Side: 25 secs; Double Side: 55 secs
Input Hopper Capacity	250 cards in a single go, can add cards while printing
Reject Tray	Available
Card Thickness	0.5 -1.0 mm thickness
Security Features	Own technology SOC, RFID ribbon, card feeder lock
User-friendliness	Easy to replace consumables
Operating Environment	Temperature: 15 - 30°C; Humidity: 35 - 95%
Storage Environment	Temperature: 5 - 45°C; Humidity: 35 - 96%
Dimensions	12.25"(L) x 13.25"(W) x 17"(H)
Weight	22 kg (48 lbs.)
Warranty	3 years, Lifetime for print head
Driver	Windows 32 and 64 bit, Windows 7,8,10
Power Supply	Auto wide ranging 100-240V, 50/60 Hz
Card Capacity	Auto Feeder: 250 cards (0.76mm thickness); Manual Feed
Cards Supported	PVC, ABSS, PET, PET-G, PC, Wooden, Translucent; 85.6 x 53.98mm (ISO ID-1/CR-80 size)
Interface	USB 2.0, Ethernet 10/100 Duplex mode
Certifications	UL, FCC, CE, KCC and CCC

Options & Consumables

Options	RFID R/W, MSR R/W, SAM R/W
Consumables	YMCK, YMCS: 500 images
	YMCKK, YMCSK, YMCFK: 400 images
	Retransfer film (500 images) with cleaning roller
Cleaning Set	Cleaning Card, Cleaning Roller and Cleaning Swabs



- XXS basic features for card design and printing with signature acquisition, data input, database view, barcodes 1D, internal document database with photo connection, database table create & edit and browse/find records. (Version bundled FOC with printer)
- XS XXS features plus QR codes, document password protection and supports .XLS, .XLSX, .CSV and .TXT database connection.
- XM XS features plus local MS Access and SQLite connection, photo on database, FaceCrop tool for face recognition and 2D barcodes.
- XL XM features plus ODBC connection, RFID contactless direct encoding, Smartcard direct encoding, Smartcard plugin, Internal and External RFID encoder support, Fingerprint acquisition, multi-layout card designs, auto-print and user allowances.
- XXL XL features plus advanced features like DESFire, Web Print Server and Net License up to 16 Pcs in the same sub-net and scope.

Email: info@bravoglobal.com www.bravoglobal.com

SCAN ME



